

In the claims:

Please cancel claim 13 and 17-21 without prejudice.

Please amend the following claims.

- A₁
1. (Currently Amended) A method[for compressing a message] comprising:
identifying a first field and a second field within [said] an electronic mail (email)
message;
applying a first set of code words to encode data in said first field; and
applying a second set of code words to encode data in said second field.
2. (Original) The method as in claim 1 further comprising:
generating said first set of code words based on the frequency with which
character strings represented by said code words are found within said first field; and
generating said second set of code words based on the frequency with which
character strings represented by said code words are found within said second field.
3. (Original) The method as in claim 2 wherein character strings which are
relatively more common within said first field are represented by relatively shorter code
words in said first set of code words and character strings which are relatively more
common within said second field are represented by relatively shorter code words in said
second set of code words.
4. (Original) The method as in claim 1 wherein said first field is an email header
field and said second field is an email text field.
- Sub
B₁

5. ~~(Original)~~ The method as in claim 1 wherein ~~said first field is an address~~
book field and said second field is an email message field.

6. (Original) The method as in claim 1 further comprising:
encoding ASCII text in said message in a 6-bit character format.

7. (Original) The method as in claim 6 further comprising:
providing one or more 6-bit escape sequences indicating that code following said
sequence represents data compressed using a particular compression technique.

8. (Original) The method as in claim 6 wherein relatively common characters
are encoded using 6 bits and relatively uncommon characters are encoded using two
successive sequences of 6 bits.

9. (Currently Amended) A method comprising:
generating a first code word table containing code words for a plurality of
character strings found in a first electronic mail (email) message field;
generating a second code word table containing code words for a plurality of
character strings found in a second email message field; and
encoding character strings in said first field using said first code word table and
character strings in said second field using said second code word table.

10. (Currently Amended) The method as in claim 9 further comprising:
initially performing a statistical analysis of character strings found in said first
email message field and said second email message field to determine a frequency of
occurrence of each of said character strings.

11. (Original) ~~The method as in claim 10 wherein character strings occurring relatively more frequently in said first field and said second field are associated with relatively shorter code words in said first code word table and said second code word table, respectively.~~

12. (Original) The method as in claim 9 wherein said first field is an email address field.

61
13. (Cancelled)

14. (Original) The method as in claim 9 further comprising:
encoding said message further using one or more alternate compression techniques.

15. (Original) The method as in claim 14 wherein one of said alternate compression techniques comprises converting ASCII characters into a 6-bit character format.

16. (Original) The method as in claim 14 wherein one of said techniques comprises identifying strings in said first or second fields based on a location of said strings in a spell-check dictionary.

17. (Cancelled)

18. (Cancelled)

19. (Cancelled)

~~20. (Cancelled)~~

21. (Cancelled)

22. (Currently Amended) A machine readable medium having program code stored thereon which, when executed by a machine, causes said machine to perform the operations of:

identifying a first field and a second field within [said] an electronic mail (email) message;

applying a first set of code words to encode data in said first field; and

applying a second set of code words to encode data in said second field.

23. (Original) The method as in claim 22 comprising additional program code to cause said processor to perform the operations of:

generating said first set of code words based on the frequency with which character strings represented by said code words are found within said first field; and

generating said second set of code words based on the frequency with which character strings represented by said code words are found within said second field.

24. (Original) The machine-readable medium as in claim 23 wherein character strings which are relatively more common within said first field are represented by relatively shorter code words in said first set of code words and character strings which are relatively more common within said second field are represented by relatively shorter code words in said second set of code words.

25. (Original) The machine-readable medium as in claim 22 wherein said first
field is an email header field and said second field is an email text field.

26. (Original) The machine-readable medium as in claim 22 wherein said first
field is an address book field and said second field is an email message field.

27. (Original) The machine-readable medium as in claim 22 comprising
additional program code to cause said processor to perform the operations of:
encoding ASCII text in said message in a 6-bit character format.

28. (Original) The machine-readable medium as in claim 27 comprising
additional program code to cause said processor to perform the operations of:
providing one or more 6-bit escape sequences indicating that code following said
sequence represents data compressed using a particular compression technique.

29. (Original) The machine-readable medium as in claim 27 wherein relatively
common characters are encoded using 6 bits and relatively uncommon characters are
encoded using two successive sequences of 6 bits.